


Safety Factor
0.000
0.250
0.500
0.750
1.000
1.250
1.500
1.750
2.000
2.250
2.500
2.750
3.000
3.250
3.500
3.750
4.000
4.250
4.500
4.750
5.000
5.250
5.500
5.750
6.000+
1.140
0.035
0.017
File Name: sezione8
SUBSTRATO ROCCIOSO
Unit Weight: 25 kN/m3
Unconfined Compressive Strength (intact): 25000 kPa
Material: COLTRE
Unit Weight: 20 kN/m3
Cohesion: 1 kPa
Friction Angle:26 degrees
Material: RIFIUTO ESISTENTE
Unit Weight: 10 kN/m3
Cohesion: 3.2 kPa
Friction Angle: 24.8 degrees
Material: RIFIUTO PROGETTO
Unit Weight: 10 kN/m3
Cohesion: 2 kPa
Friction Angle: 23 degrees
Material: MASSI CICLOPICI
Strength Type: Generalised Hoek-Brown
Unit Weight: 25 kN/m3
Material Properties
Material: BARRIERA GEOLOGICA
Unit Weight: 18 kN/m3
Cohesion: 5 kPa
Friction Angle: 16 degrees
Material: CAPPING
Unit Weight: 18 kN/m3
Cohesion: 5 kPa
Friction Angle: 16 degrees
RIFIUTO PROGETTO
CAPPING
W
W
5.00 kN/m
RIFIUTO ESISTENTE
SUBSTRATO ROCCIOSO
BARRIERA GEOLOGICA
0 m
50
100
150
200
250
300
350
400
450
500
550
600



File Name: sezione8
SUBSTRATO ROCCIOSO
Unit Weight: 25 kN/m3
Unconfined Compressive Strength (intact): 25000 kPa
Material: COLTRE
Unit Weight: 20 kN/m3
Cohesion: 1 kPa
Friction Angle:26 degrees
Material: RIFIUTO ESISTENTE
Unit Weight: 10 kN/m3
Cohesion: 3.2 kPa
Friction Angle: 24.8 degrees
Material: RIFIUTO PROGETTO
Unit Weight: 10 kN/m3
Cohesion: 2 kPa
Friction Angle: 23 degrees
Material: MASSI CICLOPICI
Strength Type: Generalised Hoek-Brown
Unit Weight: 25 kN/m3
Material Properties
Material: BARRIERA GEOLOGICA
Unit Weight: 18 kN/m3
Cohesion: 5 kPa
Friction Angle: 16 degrees
Material: CAPPING
Unit Weight: 18 kN/m3
Cohesion: 5 kPa
Friction Angle: 16 degrees